

56th St. 5600 OFFICE OF THE MARION COUNTY SURVEYOR 80 SECTION RECORD CORNER SECTION ____12_TOWNSHIP_ DATE: ____11-13-00 16 RANGE _ PARTY CHIEF: _ Wilcoxen Franklin TYPE OF MARKER: Harrrison 10 - 29 - 96METHOD OF ESTABLISHMENT: ___County: ō IN. S.P.C. E ZONE, NAD 83 16041203 511472.5994(m) 69130.1922(m) NAME: N: 3. 5. .42, 8000 140.54 W <u>56th St. 5600 N</u> 144.57 Section S. 6.

Original post set 1820 by John Hendricks with witnesses: 10" beech S 15 E 12 links, 16" dogwood N 15 W 22 links per Marion County Atlas pg. 11. Survey by O. W. Voorhis 4-12-1857 indicates no stone nor witness per Lawrence Township Legal Survey Book pg. 21. MCSO 1943 called an iron bolt. Unversaw 2-15-55 called a brass bolt. MCSO 3-27-56 called a brass bolt. MCSO 4-2-63 called a brass bolt. Wilcoxen 3-9-76 and called a brass plug. Wilcoxen 7-6-00 called a mag nail. Excavated by Wilcoxen 11-16-00 and Harrison set. (per 56th Street Construction Project.)

| REF. | DISTANCE | DESCRIPTION |
|------|----------|--|
| 1. | 65.42 | Due N to NW 7-16-5 Harrison marker |
| 2. | 33.84 | Cut 'x' E-end of inlet |
| 3. | 67.14 | Cut 'x' SE-bolt of aluminum pole base |
| 4. | 141.39' | Fort Benjamin property corner disk in concrete |
| 5. | 140.54 | Cut 'x' SE-bolt of aluminum pole base |
| 6. | 144.57 | Cut 'x' NE-bolt of aluminum pole base |
| 7. | 75.40' | Cut 'x' NE-bolt of aluminum pole base |
| 8. | 28.18' | Cut 'x' E-end of inlet |
| | | |
| | | |